

Attachment 2: Street Section Design Criteria

Criterion	Existing	Absolute	Desired	Reference
Cycle track widths	N/A	8-ft min.	10-ft	AASHTO
Vehicle lane widths				MC Road Code
Thru Lanes	11-ft	10-ft min.	11-ft	
Thru Lanes, adj to parking	10.5-ft	11-ft (with 7-ft parking)	10-ft (with 8-ft parking)	
Thru Lanes, adj to curb		11-ft		
Turn Lanes				
Two-way left-turn lane	9-ft	9-ft min. N/A	10-ft	
Parking Lane widths	7-ft	7-ft	8-ft	
Bus pad width		11-ft		
Bus pad length		90-ft		
Bus stop landing width x depth (not including curb)		5-ft x 8-ft		
Cycle track buffer width				
Adj to parking lane	N/A	2-ft	3-ft	
Adj. to travel lane	N/A	1-ft	2-ft	
Shy strip, adj. to parking	1.5-ft	2-ft		
Horizontal clearance to obstructions	1.5-ft	1.5-ft		
Sidewalk clear widths	3-ft to 10-ft	5-ft	6-ft	
Curb extension width	6-ft	4-ft	6-ft	
Landscape/BMP zone	5-ft	3-ft	5-ft	
Street Tree spacing	35-ft to 60-ft			
Café zone		8-ft		
Driveway width				
Cross slope		2% max.		
Vertical clearance				
Sidewalk		7-ft	10-ft	
Bikeway		8-ft		
Roadway		14-ft		
Utility pole dia.		18-in		